



FLOOR MAINTENANCE SYSTEMS

DAYBREAK

FLOOR COATING
EXCELLENT SHINE & DURABILITY

www.purozone.com

PRODUCT DESCRIPTION

Daybreak is an excellent, low maintenance coating. It dries to an extremely durable, high gloss shine with or without burnishing. Daybreak features outstanding resistance to scuffs, scratches, black heel marks and detergent scrubbing.



FEATURES

- Easy to apply
- Economical 16% solids
- Dries quickly
- Excellent resistance to scuffs, marks, scratches & detergents
- Durable to achieve significant labor savings
- Use when ultra high speed burnishing isn't practical

RECOMMENDED FLOOR SURFACES

- All resilient floor tile including vinyl asbestos tile
- Terrazzo, marble, quarry tile and other properly sealed hard floor surfaces

SPECIFICATIONS

Total solids: 20%	Water spotting: Good (ASTMD1793)
Non-volatile solids: 16% (ASTMD2834)	Stability: Minimum 1 year
Slip Resistance: > .50 COF	Freeze/thaw: 3 cycles (ASTMD3209)
Specular gloss: > 90	pH: 8.4 - 8.7
Dry/Recoat time: 30 minutes	Color: Milky
Recoatability: Excellent (ASTMD3153)	Odor: Acrylic
Detergent resistance: Excellent (ASTMD3207)	Coverage: 2,000 to 2,500 square feet per gallon
Removability: Very good (ASTMD1792)	Weight per gallon: 8.5 lbs.

Pur-O-Zone, Inc.
345 No. Iowa St.
P.O. Box 727
Lawrence, KS 66044-0727

CALL TOLL-FREE
1-800-727-7876

PACKAGING

ORDER NO.

6 x 1-gallon bottles per case DAYBREAK-01
5-gallon pail DAYBREAK-05

