



FLOOR MAINTENANCE SYSTEMS

SUCCESS

FLOOR COATING
ULTIMATE IN DURABILITY & WET-LOOK SHINE

www.purozone.com

PRODUCT DESCRIPTION

Success is "state of the art" technology in ultra high speed floor coating. It produces excellent gloss, with low maintenance, high speed burnishing, giving a harder, more durable, scuff & black heel resistant floor coating. Success equals lower maintenance and lower cost.



FEATURES

- Excellent wet-look with minimum burnishing
- Extremely hard, durable finish
- Excellent scuff and black heel mark resistance
- Self-sealing on most floors
- Perfect for less-than-daily ultra high speed programs
- High coverage rate

RECOMMENDED FLOOR SURFACES

- All resilient floor tile including vinyl asbestos tile
- Terrazzo, marble, quarry tile and other properly-sealed hard floor surfaces

SPECIFICATIONS

Total solids: 26%	Removability: Very good (ASTMD1792)
Non-volatile solids: 20% (ASTMD2834)	Water spotting: Excellent (ASTMD3207)
Slip resistance: > .50 COF (ASTMD2047)	Stability: Minimum 1 year
Specular gloss: > 90	Freeze/thaw: 3 cycles (ASTMD3209)
Dry/recoat time: 30 minutes or dry to touch	pH: 8.4 - 8.7 (ASTM E70)
Recoatibility: Good (ASTMD3153)	Color: Milky
Detergent resistance: Excellent (ASTMD3207)	Odor: Acrylic
	Coverage: 2,500 to 3,000 square feet per gallon
	Weight per gallon: 8.5 lbs.

Pur-O-Zone, Inc.
345 No. Iowa St.
P.O. Box 727
Lawrence, KS 66044-0727

CALL TOLL-FREE
1-800-727-7876

PACKAGING

ORDER NO.

4 x 1-gallon bottles per case	SUCCESS-01
5-gallon pail	SUCCESS-05
55-gallon drum	SUCCESS-55

