

Aqua Tuff™

Premium High-Solids Floor Finish



| | |
|---------------------|----------------------------------|
| Cleaner Type | Water-based Wood Floor Finish |
| pH | 7.0-8.0 |
| Fragrance | Minimal odor |
| Color | Light straw |
| Flammable | No |
| Stability | One year, minimum |
| Packaging | 4x1 gallon case 5-gallon pail |

| Oil-Modified Urethanes | | AQUA TUFF |
|---|-----------------------------------|---|
| Petroleum-distillate based | | Water-based |
| Strong, sharp odor | | Low odor |
| Cure time and odor continues for one or more weeks | | Floor cures and odor resolved in about 24 hours |
| Respiration devices highly recommended | | No respiration devices required during application |
| Requires mineral spirits for clean-up | Hazardous waste disposal required | Easy water clean-up |
| Solvent-saturated rags have auto-ignition potential | | Clean-up materials will not auto-ignite |
| Standard OMUs have VOC's ranging as high as 350-550+ gm/L | | Very low VOCs* of only 250 gm/L <small>Hillyard's 1907™ is another great choice. 1907 is an OMU in a waterborne formulation that has VOC levels of only 190 gm/L</small> |


*VOCs - Volatile organic compounds (VOCs) are emitted as gases from certain solids and liquids. VOCs include a variety of chemicals, some of which may have short- and long-term adverse human and environmental health effects. Many janitorial and other products contain VOCs and they are regulated. Maximum recommended exposure levels (RELs) vary by chemical. Please ask your PUR-O-ZONE representative for a copy (PDF) of the NIOSH Pocket Guide for detailed listings by chemical.

PUR-O-ZONE

purozone.com

800-727-7876

Non-flammable
Very Low VOCs
No fire or auto-ignition danger
Extends time between refinishing
Covers up to 1000 s.f./gal.
Short, 24-hour down time
1-hour between coats
29% solids



© 2010 PUR-O-ZONE, Inc.
 Read label instructions carefully