


MATERIAL AND SAFETY DATA SHEET



Success-25 High-Performance Floor Finish

Section I Company Information

Product Name: SUCCESS-25

Company Name: PUR-O-ZONE, Inc.
Address: 345 N. Iowa St., Lawrence, KS 66044
Phone/Information: 1-785-843-0771
24-Hour Emergency: 1-913-588-6633

Proper Shipping Name: Not Regulated
Generic Description: Floor Finish

Section II Hazardous Ingredients

CAS No	Ingredient	%	TLV
111773	DEG Methyl Ether	1-5	NE
78513	Tributoxyethyl Phosphate	1-5	NE

Section III Physical Data

Boiling Point: 212° F
Specific Gravity: 1.055
Vapor Pressure: Not Determined
Percent Volatiles: 75 %
Vapor Density: Less than Air
H₂O Solubility: Complete
Evaporation Rate: Slower than n-Butyl Acetate
Appearance & Odor: White milky liquid, Typical Acrylic odor
VOC: 149 g/L (1.25 Lb/gal)

Section IV Fire & Explosion Data

Flash Point: None
Extinguishing Media: Foam or carbon dioxide or dry chemical
Firefighting Procedure: Wear self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode when fighting fires.

Section V Health Hazard Data

Eyes: Can cause mild to moderate irritation.
Skin: Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.
Breathing: Excessive inhalation of vapors can cause nasal and respiratory irritation.
Swallowing: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

First Aid Procedures:

Eyes: Irrigation of the eye immediately with water for ten minutes is good safety practice.
Skin: Wash off in flow water or shower. Wash clothing before reuse.
Inhalation: Remove to fresh air if effects occur. If respiration stops, give mouth-to-mouth resuscitation. Administer oxygen if available. Call physician and/or transport to medical facility.
Ingestion: Seek medical attention. Unless advised otherwise, induce vomiting by giving either syrup of ipecac followed by 2 glass of water or by sticking finger down throat. Do not give anything by mouth if the person is drowsy, unconscious or has no gag reflex.

Section VI Reactivity Data

Hazardous Polymerization: Will not occur
Stability: Stable
Incompatibility: Avoid strong oxidizing agents

Section VII Spill & Leak Procedures

Response to spills: Stop discharge, if it can be performed safely, and contain material. If a substantial quantity is spilled, recover with pump or vacuum. Otherwise, use an absorbent material. Place contaminated material in a suitable container for disposal. Do not flush to sewer, stream or other bodies of water.

Section VIII Protective Equipment

Respiratory Protection: If TLV of the product or any component is exceeded, a NIOSH/MSHA jointly approved air supplied respirator is advised. Engineering or administrative controls should be implemented to reduce exposure.
Ventilation: Provide sufficient ventilation to maintain exposure below TLV(s).
Protective Gloves: Wear chemical resistant gloves such as nitrile rubber.
Eye Protection: Chemical splash goggles are advised.
Other Protective Equipment: Wear impervious clothing and boots.

Section IX Special Precautions

Precautions to be taken in Handling and storage: Handle with reasonable care. Avoid breathing vapors. Store in a cool dry place. Dispose of empty containers in accordance with local, state and federal guidelines. This product contains 4% DEG Methyl Ether which is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372.

Prepared: 6/04/10

Forms/MSDS/Success-25.doc

