

# Sprite® Air Scoop™ 12 & 16

Wet/Dry Tank Vacuums



## Advance

### FACT SHEET



#### STANDARD ACCESSORY

- 24 inch (60 cm) Squeegee

#### TYPICAL APPLICATIONS INCLUDE

- Schools and Universities
- Airports
- Office Buildings
- Hotels/Motels
- Convention Centers
- Maintenance Contractors
- Manufacturing Plants

With today's high cost of labor, why waste time with mops and buckets? Put a Sprite® Air Scoop™ on the job and start saving money.

The Sprite Air Scoop is available in 12 gallon (45 L) or 16 gallon (60 L) tank sizes. It has a rugged, rotationally molded polyethylene tank that is corrosion proof and will not chip or dent. It is hinged so it conveniently pivots to dump its contents: or drains with a built in hose. The entire tank lifts off for cleaning and allows total access for motor service or maintenance.

A 1.3 hp 2-stage, by-pass motor is powerful yet a quiet 70 dB A. A Float system stops recovery to prevent tank overflow.

For dry pick up, insert a sock filter or a reusable cloth bag, and use any of the dry pick up accessories. A washable exhaust filter helps assure dust containment.

Much faster than picking up water with a hose and wand, the Sprite Air Scoop models are especially effective in tight spots too. The 24 inch (60 cm) front-mounted squeegee maneuvers right up to walls and into corners, picking up either in forward or reverse. A simple floor pedal raises or lowers the squeegee, which is spring loaded to follow floor contours for thorough results.



# Advance Sprite® Air Scoop™ 12 & 16

## Wet/Dry Tank Vacuums



Roto-molded poly tank is hinged for tip and pour emptying. Also has a drain hose



A sock filter goes over the float assembly for dry pick up, and an optional reusable cloth bag can be inserted into the tank for dry vacuum operation



Simple design gives direct access to modular vac motor. Four bolts and motor is released for service or replacement



Large rear wheels make transport easy, even up or down stairs

To empty the tank, either tip and pour out the contents or use the convenient drain hose at the rear

A built in float system automatically cuts off the vacuum air flow when the tank fills with liquid, preventing overflow

A cleanable, reusable filter keeps exhaust air clean and muffles vac motor sound

Tough polyethylene construction and functional design assure durability, dependability

Optional 8 piece wet or dry pick-up tool kits are available for complete versatility

A sock filter goes over the float assembly for dry pick up, and a cloth bag can be inserted into the tank for dry vacuum operation

Tank can be lifted off for clean-out, emptying or for service access to motor

The Sprite® Air Scoop™ includes a squeegee that works in forward and reverse, and is spring-loaded to follow uneven floor contours



## Defining Cleaning Innovation...

- Our products are designed using innovative technology that increases productivity and drives down the cost to clean.
- You can get expert service and maintenance for your Advance machines from factory-trained personnel around the world. Fast parts delivery, too.
- Maintain peak performance with Nilfisk Genuine OEM Parts.

Nilfisk Genuine OEM Parts

**Only 70 dB A at operator's position**

## Technical Specifications

Model	Sprite® Air Scoop™ 12	Sprite® Air Scoop™ 16
<b>Motor</b>	1.3 hp, 115 V / 60 Hz, 2-stage	1.3 hp, 115 V / 60 Hz, 2-stage
<b>Air Flow</b>	91 ft <sup>3</sup> /min (2,577 L/min)	91 ft <sup>3</sup> /min (2,577 L/min)
<b>Sealed Water Lift</b>	88 in (223 cm)	88 in (223 cm)
<b>Squeegee Width</b>	24 in (61 cm) Air Scoop 30 in (76 cm) (optional) Air Scoop	24 in (61 cm) Air Scoop 30 in (76 cm) (optional) Air Scoop
<b>Sound Level</b>	70 dB A	70 dB A
<b>Construction</b>	roto-molded polyethylene tank	roto-molded polyethylene tank
<b>Tank Capacity</b>	12 gal (45 L) actual	16 gal (60 L) actual
<b>Wheels</b>	10 in x 1.75 (25 x 4.5 cm) main 4 in x 1 in (10 x 2.5 cm) casters	10 in x 1.75 (25 x 4.5 cm) main 4 in x 1 in (10 x 2.5 cm) casters
<b>Power Cable</b>	50 ft (15 m)	50 ft (15 m)
<b>Dimensions</b>	Height – 32 in (81 cm) Width – 17 in (43 cm) Length – 40.5 in (103 cm) Height (dome) – 32 in (81 cm) Height handle – 39.5 in (100 cm)	Height – 35 in (89 cm) Width – 17 in (43 cm) Length – 40.5 in (103 cm) Height (dome) – 35 in (89 cm) Height handle – 39.5 in (100 cm)
<b>Net Weight</b>	72 lb (33 kg)	77 lb (35 kg)
<b>Shipping Weight</b>	80 lb (36 kg) Air Scoop	85 lb (39 kg) Air Scoop
<b>Part Number</b>	56 209 091	56 209 092

Specifications are subject to change without notice.



14600 21st Avenue North  
Plymouth, MN 55447-3408  
www.advance-us.com  
Phone: 800-850-5559  
Fax: 800-989-6566

240 Superior Boulevard  
Mississauga, Ontario, Canada L5T 2L2  
www.nilfisk-advance.com  
Phone: 905-564-1149 or 800-668-8400  
Fax: 905-564-1030 or 800-263-5111

©2009, Nilfisk-Advance, Inc.,  
Printed in U.S.A., Form L2288A, 6-09

